



6" x 2" x 1/4" RAILS
W/ 1/2" x 2" WEARSTRIP

REINFORCING PLATE
1/4" PL x 1'-9 1/4" x 4' TALL
(TYP. BOTH SIDES)

FLOOR:
3" CHANNEL x 4.1# ON 12" C &
1/4" PL - STRUCTURAL EQUIVALENT

PAINTING:
(2) COATS OF CHASSIS SAVER
(2) COATS OF ENAMEL

NOTE:
ALL WELDS TO BE FULL WELDS.

50 CU YD CLOSED TOP BOX

CATTARAUGUS COUNTY
DEPARTMENT OF PUBLIC WORKS

SCALE: 3/8" = 1' DATE: 4/27/2016

DWG. M.R.S. DGN. TRACE CK.

PUSH PL
1/4 x 48" x 52"
BOXED IN

REINFORCING PLATE
3/16" PL x 1'-9 1/4" x 4' TALL
(TYP. BOTH SIDES)

HOOK FOR SAFETY CHAINS, TYP.
BOTH SIDES. HOOK ON OPPOSITE
SIDE IS A KEY HOLE TYPE TO BE
LOCATED SO THAT IT HOLDS THE
DOOR IN THE OPEN POSITION

3" x 5" x 7 GA.
4-WAY BEND SIDE

GREASE FITTINGS
(TYP. BOTH SIDES)

3" x 3" x 10 GA. PL @ 45°,
REAR DOOR ONLY, TYPICAL
EACH CROSS SUPPORT BAR

